



### Electrical specifications

|                           |             |
|---------------------------|-------------|
| Model no.                 | TLVPGF14PCM |
| DLC ID                    | -           |
| Power $\pm 10\%$          | 14W         |
| Input voltage             | 120 VAC     |
| Frequency                 | 50/60 Hz    |
| Efficacy $\pm 3\%$        | 75 lm/W     |
| Power factor              | >0.5        |
| Dimmable                  | 0-10 V      |
| Surge protection          | 2.5 kv      |
| Total harmonic distortion | <20%        |

### Photometric specifications

|                        |         |
|------------------------|---------|
| CRI                    | >70     |
| CCT                    | 5000K   |
| Beam angle             | 120°    |
| Light output $\pm 3\%$ | 1061 lm |

### Mechanical specifications

|                       |   |
|-----------------------|---|
| IP rating             | Wet locations   |
| Material              | Die cast aluminum   |
| Lens                  | Glass   |
| Net weight            | -   |
| Product dimensions    | $\pm 4.375" \times 9.25"$<br>$\pm 111.13 \text{ mm} \times 234.95 \text{ mm}$ |
| Operating humidity    | -   |
| Operating temperature | -40°C ~ 40°C  |
| Lumen maintenance     | -   |

### Product description:

- Compliant with standards:
  - UL 1598
  - CSA C22.2 No. 250.0
- Optimal durability and heat dissipation.
- 1/2" threaded opening for conduit passage.

### Applications:

Commercial areas, parking lots, garages, security lighting, entrances, doors, industrial facilities, walkways and perimeters, etc.