



## Specifications TLVPUS4F48ADS

### Electrical Specifications

Model No.	TLVPUS4F48ADS
DLC ID	S-SGBFDE
Power (W) selectable $\pm 10\%$	35 W / 40 W / 48 W
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy $\pm 3\%$	133.1 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	<15%

### Photometric Specifications

CRI	84	
Selectable CCT	4000K / 5000K / 6500K	
Beam angle	120°	
Light Output $\pm 3\%$	35W: 4658.5 lm	40W: 5324 lm
	48W: 6388.8 lm	
Dimmable	0-10V	

### Mechanical Specifications

IP Rating	IP66 / NEMA 4X
Material	Polycarbonate
Lens	Frosted
Poids Net	2.1 kg
Product size (mm)	$\pm 1\ 211 \times 102 \times 85$ mm
Product size (inch)	$\pm 47.68" \times 4.02" \times 3.35"$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 40°C
Lumen maintenance	>81% at 100 000 hours

## Product Description:

- Large supply voltage range 120-347V.
- Selectable CCT and power.
- Lightweight body material, corrosion resistant, waterproof and dustproof.
- Easy installation with fast connection design, shorten the installation process and save labor cost.
- Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
- Saves up to 60% in electricity consumption compared to fluorescent lighting fixture.
- Body and diffuser could meet the IK10 test requirement.
- Warranty: 5 Years.
- Built-in motion and light sensor.

## Applications:

Suitable for farm, food processing sector, warehouse, wet locations etc.

### Optional accessory

