



Specifications TLWLC200P

Electrical Specifications

Model no.	TLWLC200P
Power (W) ±10%	200 W
Input voltage (V)	AC100-277V, 50/60Hz
Efficacy ±3%	120 lm/W
Power factor (PF)	0.9

Photometric Specifications

CRI	80
CCT	5 000 K
Beam angle	360°
Light output ±3%	24 000 lm
Dimmable	No

Mechanical Specifications

IP rating	Damp locations
Material	PC / Aluminum / Stainless steel
Lens	Clear PC
Net weight	N/A
Product size (mm)	± Ø 165 mm x 368 mm
Product size (inch)	± Ø 6.5" x 14.5"
Operating temperature	-40°C ~ 60°C
Operating humidity	10% ~ 90%
Lumen maintenance	>80% at 100 000 hours

Product Description:

- Stainless steel guard for safety protection. Can be used directly on the floor.
- Integrated NEMA5-15R receptacle. Can connect in series up to 3 pieces.
- With approximately 35 ft power cord. (≈ 10 668 mm)
- 50% / 100% / OFF switch.
- Portable hook. Easy to carry and install.
- Long lifespan up to 50 000 hours.
- More powerful than a traditional 400 W temporary lamp.
- 10 000 V high voltage surge protection.
- Other CCT available on special request.

Applications:

Construction areas, temporary site, different scale working places, repair workshop, warehouse, indoor and outdoor etc.