



Specifications TLWMAU150BP

Electrical Specifications

Model No.	TLWMAU150BP
DLC ID	S-XFMT10
Power (W) $\pm 10\%$	150 W (DLC: 149.7)
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy $\pm 3\%$	130.71 lm/W
Power Factor (PF)	0.96

Photometric Specifications

CRI	72
CCT	5 000 K
Beam angle	140°
Light Output $\pm 3\%$	19 573 lm
Dimmable	No

Mechanical Specifications

IP Rating	IP65
Material	Aluminium
Lens	PC
Poids Net	7.9 kg
Product size (mm)	512 x 277 x 160 mm
Product size (inch)	$\pm 20.2 \times 10.9 \times 6.3$ in
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C
Lumen maintenance	>77% at 100 000 hours

Product Description:

- Replace 400 W MH or HPS lighting.
- Mounts on wall or pole, accessories included.
- A dusk-to-dawn photocell provides automatic on/off. Photocell included.
- Bracket included.
- Waterproof and dustproof.
- Saves in electricity consumption compared to MH and HPS lighting fixture.
- Warranty: 5 Years.

Applications:

Dusk-to-dawn light.
Provides general purpose area, security, roadway and landscape lighting.
Used for outdoor lighting: factories, warehouses, farms, etc.