



Specifications TLWMAUS80ASL

Electrical Specifications

Model No.	TLWMAUS80ASL
DLC ID	N/D
Power(W) selectable $\pm 10\%$	40W / 60W / 80W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor (PF)	0.9
Surge protection	4 Kv
Total harmonic distortion	<20%
Dimmable	0-10V

Photometric Specifications

CRI	≥ 80
CCT selectable	3500K / 4000K / 5000K
Beam angle	120°
Light Output $\pm 3\%$	40W: 5200 lm 60W: 7800 lm
	80W: 10400 lm

Mechanical Specifications

IP Rating	IP65
Material	Aluminum + PC
Lens	Frosted
Net Weight	1.74 kg
Product size (mm)	$\pm 345 \times 266 \times 103$ mm
Product size (inch)	$\pm 13.6" \times 10.5" \times 4.05"$
Operating Humidity	10% à 90%
Operating Temperature	-30°C à 45°C
Lifespan (L70)	50 000 hours

Product Description:

- Selectable power and CCT.
- Replace 250 W MH or HPS lighting.
- Mounts on wall or pole, accessories included.
- A dusk-to-dawn photocell provides automatic on/off. Photocell included.
- Bracket included.
- Waterproof and dustproof.
- Saves in electricity consumption compared to MH and HPS lighting fixture.
- Warranty: 5 Years.

Applications:

Dusk-to-dawn light.

Provides general purpose area, security, roadway and landscape lighting.

Used for outdoor lighting: factories, warehouses, farms, etc.