



Specifications TLWMBU40ABK

Electrical Specifications

Model No.	TLWMBU40ABK
DLC ID	PLDQ0F6SCVT7
Power (W) ± 10%	40 W (DLC: 40.52 W)
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	124.01 lm/W
Power Factor (PF)	0.937
Surge protection	4 Kv
Total harmonic distortion	≤10%

Photometric Specifications

CRI	72.4
CCT selectable	3000K / 4000K / 5000K
Beam angle	Type II
Light Output ± 3%	5 024.6 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	Polycarbonate
Net Weight	2.16 kg
Product size (mm)	± 216 x 281 x 112 mm
Product size (inch)	± 8.5 x 11.05 x 4.41 in
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lumen maintenance	>77% at 100 000 hours

Product Description:

- Large supply voltage range 120-347V.
- 3000K / 4000K / 5000K selectable CCT.
- Adjustable direction from 0 to 90 degrees.
- Die cast aluminum housing provides solid mounting to wall.
- Optional photocell.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.
- Compatible with most sensors.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.