



## Specifications TLWMBUS20ABK

### Electrical Specifications

Model No.	TLWMBUS20ABK
DLC ID	S-Q9R77S
Power (W) selectable $\pm 10\%$	8W / 10W / 15W / 20W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	150 lm/W
Power Factor (PF)	0.962
Surge protection	N/A
Total harmonic distortion	<15%

### Photometric Specifications

CRI	73
CCT selectable	3000K / 4000K / 5000K
Beam angle	Type II
Light Output $\pm 3\%$	8W: 1 200 lm    10W: 1 500 lm
	15W: 2 250 lm    20W: 3 000 lm

### Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	Polycarbonate
Net Weight	N/A
Product size (mm)	$\pm 165 \times 197 \times 130$ mm
Product size (inch)	$\pm 6.5" \times 7.77" \times 5.14"$
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lumen maintenance	>79% at 100 000 hours

## Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Built-in photocell.
- Adjustable direction from 0 to 90 degrees.
- Die cast aluminum housing provides solid mounting to wall.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.