



## Specifications TLWMBUS60ABK

### Electrical Specifications

Model No.	TLWMBUS60ABK
DLC ID	S-WN04M7
Power (W) selectable $\pm 10\%$	30W / 40W / 50W / 60W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	150 lm/W
Power Factor (PF)	0.946
Surge protection	N/A
Total harmonic distortion	<15%

### Photometric Specifications

CRI	74
CCT selectable	3000K / 4000K / 5000K
Beam angle	Type II
Light Output $\pm 3\%$	30W: 4 500 lm    40W: 6 000 lm
	50W: 7 500 lm    60W: 9 000 lm

### Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	Polycarbonate
Net Weight	N/A
Product size (mm)	$\pm 216 \times 234.6 \times 154$ mm
Product size (inch)	$\pm 8.5" \times 9.24" \times 6.07"$
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lumen maintenance	>75% at 100 000 hours

## Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Built-in photocell.
- Adjustable direction from 0 to 90 degrees.
- Die cast aluminum housing provides solid mounting to wall.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.

## Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.