



Specifications TLWMDU1018ABK

Electrical Specifications

Model No.	TLWMDU1018ABK
DLC ID	N/D
Power (W) ± 10%	10 W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy ± 3%	105 lm/W
Power Factor (PF)	>0.9
Surge protection	2.5 kv
Total harmonic distortion	N/A

Photometric Specifications

CRI	>80
CCT selectable	3 000 K / 4 000 K / 5 000 K
Beam angle	18°
Light Output ± 3%	1 050 lm
Dimmable	0-10 V

Mechanical Specifications

IP Rating	Damp locations
Material	Aluminum
Lens	Acrylic
Net Weight	0.95 kg
Product size (mm)	± Ø108 x 170.25 x 168 mm
Product size (inch)	± Ø4.3" x 6.7" x 6.6"
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 40°C
Lumen maintenance	>64% at 100 000 hours

Product description:

- Down lighting (10W).
- Selectable CCT.
- Built-in photocell.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, corridors, staircases, etc. Indoor and outdoor.

