



Specifications TLWMFUS40ABK

Electrical Specifications

Model No.	TLWMFUS40ABK
DLC ID	N/D
Power (W) selectable $\pm 10\%$	15W / 20W / 30W / 40W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor (PF)	≥ 0.9
Surge protection	L-N: 2 KV L/N-PE: 4 KV
Total harmonic distortion	<20%
Dimmable	0-10V

Photometric Specifications

CRI	>70	
CCT selectable	3000K / 4000K / 5000K	
Beam angle	Type IV	
Light Output $\pm 3\%$	15W: 1950 lm	20W: 2600 lm
	30W: 3900 lm	40W: 5200 lm

Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	PC
Net Weight	2.40 kg
Product size (mm)	$\pm 320.4 \times 187.5 \times 130.2$ mm
Product size (inch)	$\pm 12.61" \times 7.38" \times 5.13"$
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C
Lifespan (L70)	54 000 hours

Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Lens type II, type III and type IV available.
- Die cast aluminum housing provides solid mounting to wall.
- Built-in photocell .
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.