



### Specifications TLWMM14WBK

#### Electrical Specifications

|                           |                  |
|---------------------------|------------------|
| Model No.                 | TLWMM14WBK       |
| DLC ID                    | N/D              |
| Power (W)                 | 14 W             |
| Input Voltage (V)         | AC 120V, 50/60Hz |
| Efficacy ± 3%             | 115 lm/W         |
| Power Factor (PF)         | ≥0.9             |
| Total harmonic distortion | <20%             |
| Surge protection          | 4 Kv             |
| Dimmable                  | Non              |

#### Photometric Specifications

|                   |          |
|-------------------|----------|
| CRI               | ≥70      |
| CCT               | 3 000 K  |
| Beam angle        | 120°     |
| Light Output ± 3% | 1 610 lm |

#### Mechanical Specifications

|                       |                         |
|-----------------------|-------------------------|
| IP Rating             | IP65                    |
| Material              | Aluminum                |
| Lens                  | PC                      |
| Net Weight            | N/A                     |
| Product size (mm)     | ± 211.6 x 144 x 71.6 mm |
| Product size (inch)   | ± 8.33" x 5.67" x 2.82" |
| Operating Humidity    | 10% - 90%               |
| Operating Temperature | -40°C ~ 45°C            |
| Lifespan (L70)        | N/A                     |

### Product Description:

- Die cast aluminum housing provides solid mounting to wall.
- Built-in photocell.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.
- It could be fit with sensor.

### Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.