



Specifications TLWMMUS25ABK

Electrical Specifications

Model No.	TLWMMUS25ABK	
DLC ID	S-1HLYMX	
Power (W) selectable ±10%	10W / 18W / 25W	
Input Voltage (V)	AC 120/347V, 50/60Hz	
Efficacy ± 3%	134.6 lm/W	
Power Factor (PF)	0.9	
Total harmonic distortion	15%	
Surge protection	L-N: 1KV, L/N-Pe: 2KV	
Dimmable	0-10 V	

Photometric Specifications

CRI	83	
CCT selectable	3000K / 4000K / 5000K	
Beam angle	120°	
Light Output ± 3%	10W: 1 346 lm	18W: 2 422.8 lm
	25W: 3 365 lm	

Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	PC
Net Weight	N/A
Product size (mm)	± 211.6 x 144 x 71.6 mm
Product size (inch)	± 8.33" x 5.67" x 2.82"
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 45°C
Lifespan (L70)	N/A

Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Built-in photocell.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.
- It could be fit with sensor.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.