



Specifications TLWMO12PBK

Electrical Specifications

| | |
|---------------------------|----------------------|
| Model No. | TLWMO12PBK |
| DLC ID | N/D |
| Power (W) ± 10% | 12 W |
| Input Voltage (V) | AC 120-277V, 50/60Hz |
| Efficacy ± 3% | 85 lm/W |
| Power Factor (PF) | 0.9 |
| Surge protection | N/D |
| Total harmonic distortion | N/D |

Photometric Specifications

| | |
|-------------------|----------|
| CRI | ≥80 |
| CCT | 5 000 K |
| Beam angle | N/D |
| Light Output ± 3% | 1 020 lm |
| Dimmable | 0-10V |

Mechanical Specifications

| | |
|-----------------------|------------------------|
| IP Rating | IP65 |
| Material | Aluminum |
| Lens | Clear (PC) |
| Net Weight | N/D |
| Product size (mm) | 160 x 265 x 98 mm |
| Product size (inch) | ± 6.3" x 10.4" x 3.86" |
| Operating Humidity | 10% - 90% |
| Operating Temperature | -25°C ~ 40°C |

Product Description:

- Die cast aluminum housing provides solid mounting to wall.
- Photocell included. ON / OFF selectable.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
Other colors available on special request.
- Warranty: 5 Years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, hotels, etc.