



### Specifications TLWMTUS120ABK

#### Electrical Specifications

Model No.	TLWMTUS120ABK
DLC ID	S-KXCZ09
Power (W) selectable $\pm 10\%$	60W / 90W / 120W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor	0.9
Surge protection	N/D
Total harmonic distortion	$\leq 15\%$
Dimmable	0-10V

#### Photometric Specifications

CRI	83	
CCT selectable	2200K / 3500K / 5000K	
Beam angle	120°	
Light Output $\pm 3\%$	60W: 7800 lm	90W: 11 700 lm
	120W: 15 600 lm	

#### Mechanical Specifications

IP Rating	IP65
Material	Aluminum + PC
Lens	Frosted
Net Weight	N/D
Product size (mm)	$\pm 360.4 \times 235.5 \times 189$ mm
Product size (in)	$\pm 14.2" \times 9.3" \times 7.44"$
Operating Humidity	10% to 90%
Operating Temperature	-30°C to 45°C
Lumen maintenance	$>77\%$ at 100 000 hours

### Product description:

- Wide supply voltage range 120-347V.
- Selectable power and CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Photocell included.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black
- Warranty: 5 years.

### Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, hotels, etc.



Selectable CCT  
(2 200 K / 3 500 K / 5 000 K)



Selectable Watt  
(60 W / 90 W / 120 W)



Built-in photocell