



Specifications TLWMTUS40ABK

Electrical Specifications

Model No.	TLWMTUS40ABK
DLC ID	S-SVKQ02
Power (W) selectable $\pm 10\%$	15W / 20W / 30W / 40W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	121.6 lm/W
Power Factor	0.934
Surge protection	N/A
Total harmonic distortion	<15%
Dimmable	0-10V

Photometric Specifications

CRI	83
CCT selectable	2200K / 3500K / 5000K
Beam angle	120°
Light Output $\pm 3\%$	15W: 1 824 lm 20W: 2 432 lm 30W: 3 648 lm 40W: 4 864 lm

Mechanical Specifications

IP Rating	IP65
Material	Aluminum + PC
Lens	Frosted
Net Weight	N/A
Product size (mm)	$\pm 360.4 \times 235.5 \times 189$ mm
Product size (in)	$\pm 14.2" \times 9.3" \times 7.44"$
Operating Humidity	10% to 90%
Operating Temperature	-30°C to 45°C
Lumen maintenance	N/A

Product description:

- Wide supply voltage range 120-347V.
- Selectable power and CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Photocell included.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black
- Warranty: 5 years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, hotels, etc.



Selectable CCT
(2 200 K / 3 500 K / 5 000 K)



Selectable Watt
(15 W / 20 W / 30 W / 40 W)



Built-in photocell