



Specifications TLWMTUS40ABK

Electrical Specifications

Model No.	TLWMTUS40ABK
DLC ID	S-SVKQ02
Power (W) selectable $\pm 10\%$	15W / 20W / 30W / 40W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	150 lm/W
Power Factor	0.934
Surge protection	N/A
Total harmonic distortion	<15%
Dimmable	0-10V

Photometric Specifications

CRI	83		
CCT selectable	2200K / 3500K / 5000K		
Beam angle	T3		
Light Output $\pm 3\%$ 2200K	15W: 1800 lm	20W: 2400 lm	
	30W: 3600 lm	40W: 4800 lm	
Light Output $\pm 3\%$ 3500K	15W: 2100 lm	20W: 2800 lm	
	30W: 4200 lm	40W: 5600 lm	
Light Output $\pm 3\%$ 5000K	15W: 2250 lm	20W: 3000 lm	
	30W: 4500 lm	40W: 6000 lm	

Mechanical Specifications

IP Rating	IP65
Material	Aluminum + PC
Lens	Frosted
Net Weight	N/A
Product size (mm)	$\pm 360.4 \times 235.5 \times 189$ mm
Product size (in)	$\pm 14.2" \times 9.3" \times 7.44"$
Operating Humidity	10% to 90%
Operating Temperature	-30°C to 45°C
Lumen maintenance	N/A

Product description:

- Wide supply voltage range 120-347V.
- Selectable power and CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Photocell included.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black
- Warranty: 5 years.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, hotels, etc.



Selectable CCT
(2 200 K / 3 500 K / 5 000 K)



Selectable Watt
(15 W / 20 W / 30 W / 40 W)



Built-in photocell