



Selectable CCT and power



Specifications TLWMUS60ABK

Electrical Specifications

Model No.	TLWMUS60ABK
DLC ID	N/D
Power (W) selectable $\pm 10\%$	30W / 40W / 50W / 60W
Input Voltage (V)	AC 120-347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor (PF)	0.9
Total harmonic distortion	<15%
Dimmable	No

Photometric Specifications

CRI	≥ 70
CCT selectable	3000K / 4000K / 5000K
Beam angle	120°
Light Output $\pm 3\%$	30W: 3 900 lm
	40W: 5 200 lm
	50W: 6 500 lm
	60W: 7 800 lm

Mechanical Specifications

IP Rating	IP65
Material	Aluminum
Lens	Glass
Net Weight	3.9 kg
Product size (mm)	$\pm 360 \times 235.5 \times 186$ mm
Product size (inch)	$\pm 14.17" \times 9.27" \times 7.28"$
Operating Humidity	10% - 90%
Operating Temperature	-30°C ~ 45°C
Lumen maintenance	>79% at 100 000 hours

Product Description:

- Large supply voltage range 120-347V.
- Selectable power and CCT.
- Die cast aluminum housing provides solid mounting to wall.
- Built-in photocell.
- Saves on electricity consumption compared to conventional lighting fixture.
- Color: black.
- Warranty: 5 Years.
- It could be fit with sensor.

Applications:

Perimeter lighting for safety and security. Use on factories, warehouses, commercial buildings, etc.