



Electrical specifications	
Model no.	TPHBUS150AWHD
DLC ID	S-BSP2DF
Power ±10%	100 W / 120 W / 150 W
Input voltage	120-347 V
Frequency	50/60 Hz
Efficacy ±10%	150 lm/W
Power factor	≥0.9
Dimmable	0-10 V
Surge protection	6 kv
Total harmonic distortion	15%

Photometric specifications	
CRI	81
CCT	3 500 K / 4 000 K / 5 000 K
Beam angle	90°
Light output	100W: 15 000 lm
	120W: 18 000 lm
	150W: 22 500 lm

Mechanical specifications	
IP rating	IP65
Impact resistance	IK08
Material	Aluminum
Lens	Polycarbonate
Net weight	2 kg
Product dimensions	± Ø9.06" x 4.68"
	± Ø228.6 x 101.6 mm
Operating humidity	10% ~ 90%
Operating temperature	-40°C ~ 50°C
Lumen maintenance	>80% at 100 000 hours

### Product description:

- Selectable power and CCT.
- Lightweight materials for easy installation.
- UGR <28.
- 600 mm stainless steel suspension kit included.
- 2 meters power cable.
- Saves up to 70% energy compared to conventional lighting.

### Utilisations:

Warehouses, workshops, garages, industry, arenas and other high-ceilinged areas.

Accessoires en option			
			
<b>HD07VR-MH-WH</b>	<b>HD07VR-PH-WH</b>	<b>TPHBPMA-WH</b>	<b>HD06R</b>
Microwaves motion sensor	PIR motion sensor	Suspended mounting bracket	Remote control for motion sensor
			
<b>TPHB1AR</b>	<b>TPHBPMB-WH</b>	<b>TPHB1LS</b>	<b>TPHB1LC</b>
Aluminum reflector	Suspended mounting box	PC reflector	PC reflector cover
			
<b>TPHB1WG</b>	<b>TPHBTU-WH</b>	<b>BLD-RM30R</b>	
Protective grid	"U" bracket	Emergency lighting battery 100/347 V (Optional remote)	