




Pictures for illustration purpose only.



Specifications TLPBLUS22W35AD

Electrical Specifications

Model No.	TLPBLUS22W35AD
DLC ID	PLZV2L0TS9LH
Power (W) tunable	20W - 25W - 30W - 35W
Input Voltage (V)	AC100-347V, 50/60Hz
Efficacy $\pm 3\%$	130 lm/W
Power Factor (PF)	0.9
Total Harmonic Distortion	$\leq 15\%$

Photometric Specifications

CRI	80
CCT tunable	3000K - 3500K - 4000K - 5000K
Beam Angle	120°
Light Output $\pm 3\%$	20W: 2600 lm 25W: 3250 lm 30W: 3900 lm 35W: 4550 lm
Dimmable	0-10 V

Mechanical Specifications

IP Rating	IP40
Material	Aluminum
Lens	Frosted PC
Net Weight	2.5 kg
Product size (mm)	603 x 603 x 30 mm
Product size (in)	$\pm 24 \times 24 \times 1.2$ in
Operating Humidity	10% - 90%
Operating Temperature	-20°C ~ 50°C
Lifespan (L70)	60 000 hours



Product Description:

- Backlight LED panel luminaire.
- Tunable power and CCT with a switch.
- Installation: suspended / suspended ceiling / surface mount with optional mounting frame.
- "IC" type
- 0-10 V variable intensity and compatible with most 0-10 V dimmer models.
- Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
- Uniform brightness, high performance, low energy consumption and low radiant heat.
- Warranty: 5 Years.

Applications:

Office, business place, clinic, airport, commerce, hotel, basement, etc.