


RoHS


Specifications TLVPU5F72ND

Electrical Specifications

Model No.	TLVPU5F72ND
DLC ID	PP055J7F
Power (W) ± 10%	72 W (DLC: 71.4 W)
Input Voltage (V)	AC120-347V, 50/60Hz
Efficacy ± 3%	135.01 lm/W
Power Factor (PF)	0.934
Total harmonic distortion	16.7%

Photometric Specifications

CRI	82.8
CCT	4 000 K
Beam angle	120°
Light Output ± 3%	9 640 lm
Dimmable	0-10V

Mechanical Specifications

IP Rating	IP66 / NEMA 4X
Material	Polycarbonate
Lens	Frosted
Net Weight	3.02 kg
Product size (mm)	1 560 x 120 x 108 mm
Product size (inch)	± 61-3/8 x 4-11/16 x 4-1/4"
Operating Humidity	10% - 90%
Operating Temperature	-35°C ~ 45°C
Lifespan (L70)	54 000 hours

Product Description:

- Lightweight body material, corrosion resistant, waterproof and dustproof.
- Easy Installation with fast connection design, shorten the installation process and save labor cost.
- Perfect replacement for the whole set of T8 and T5 fluorescent lighting fixture.
- Save up to 60% in electricity consumption compared to fluorescent lighting fixture.
- Body and diffuser could meet the IK08 test requirement.
- Warranty: 5 Years.
- It could be fitted with sensor.
- Other CCT available on special request.
- Clear lens available separately.
- Polycarbonate fasteners included.

Applications:

Suitable for farm, food processing sector, warehouse, wet locations etc.